

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
23 September 2004 (23.09.2004)


PCT

(10) International Publication Number
WO 2004/081262 A1

- (51) International Patent Classification⁷: C25D 7/12, 5/18, H05K 3/24
- (21) International Application Number: PCT/EP2004/002208
- (22) International Filing Date: 4 February 2004 (04.02.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
103 11 575.7 10 March 2003 (10.03.2003) DE
- (71) Applicant (for all designated States except US):
ATOTECH DEUTSCHLAND GMBH [DE/DE];
Erasmusstrasse 20, 10553 Berlin (DE).
- (72) Inventors; and
(75) Inventors/Applicants (for US only): REENTS, Bert
[DE/DE]; Bötzwstrasse 31, 10407 Berlin (DE). MAG-
AYA, Tafadzwa [ZW/DE]; Sickingenstrasse 77, 10553
Berlin (DE).
- (74) Agent: EFFERT, BRESSEL UND KOLLEGEN;
Radickestrasse 48, 12489 Berlin (DE).
- (81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.
- (84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: METHOD OF ELECTROPLATING A WORKPIECE HAVING HIGH-ASPECT RATIO HOLES



(57) Abstract: In order to electroplate workpieces comprising high-aspect ratio holes a method is disclosed comprising the steps bringing the workpiece and at least one anode into contact with a metal plating electrolyte, and applying a voltage between the workpiece and the anodes, to the effect that a current flow is provided to the workpiece. The current flow is a pulse reverse current flow having a frequency of at most about 6 Hertz. According to the frequency each cycle time comprises at least one forward current pulse and at least one reverse current pulse.